



Event Studies – UMR Locks 27



- The Locks and Dam 27 project is located at Mississippi River mile 185.5, between the confluence of the Missouri River (RM 195.5) and downtown St. Louis, Missouri (RM 179-180).
- The project has two parallel locks along the left descending bank: a 1200' x 110' main chamber and a 600' x 110' auxiliary chamber. The twin locks are situated at the southern end of an 8.4 mile long man made canal.
- The navigation pool is 27.8 miles long and covers 13,000 acres. The project was put into service in 1953.



US Army Corps of Engineers

UMR Locks 27 and Chain of Rocks Canal






One Team: Relevant, Ready, Responsive and Reliable



UMR-IWW NAVIGATION SYSTEM




US Army Corps of Engineers^a





Locks 27 Tonnage 1992-2005








Lock 27 Main Chamber in 2004 (66.5 million tons)








US Army Corps Lock 27 Auxiliary Chamber in 2004 (4.7 million tons)









- 26 July 10 August 2004
 - Closure of main lock chamber at Lock 27, Mississippi River mile 185.0 for maintenance repairs. Auxiliary lock chamber remained open and available to river traffic during this period.
- February March 2005
 - Surveys of shippers and carriers were conducted regarding impacts of this closure. Those surveyed included:
 - Shippers who moved more than 50,000 tons thru Locks 27 in 2003. A total of 206 companies were surveyed, which accounted for about 80 % of the total traffic.
 - ◆ Carriers with a frequency of 50 or more trips through Locks 27 in 2003, and carriers who transported more than 1,000 tons through Lock 27 in 2003. A total of 22 companies were surveyed.





- Purpose of survey was to identify total costs incurred, and operational changes made by industry associated with the closure event.
- The overall response rate was 39 % for the shippers survey and 68 % for the carriers survey, which was largely the result of the follow up telephone campaign and contacts made with industry groups (MARC 2000 and the Waterway Council, Incorporated).





Shippers

- Over 70 % reported no change in procedures was necessary. This was credited to advance notification and the auxiliary chamber remaining in service, minimizing disruption.
- About 10 % decided to stockpile product and wait for traffic to clear; about 6 % switched to all-overland mode for product delivery.





Carriers

- All but one of the responding companies indicated that notification of the scheduled closure was adequate.
- Majority of the companies reacted to the closure by having towboats remain in queue, or by breaking tows to lock through the auxiliary lock.
- Several companies participated in industry self help.





- Cost of closure
 - Shippers Majority indicated no additional cost incurred.
 - Carriers Estimated \$3.9 million cost of closure, mostly attributed to delay cost and lost revenue.



Analysis of OMNI Data



- Because tows were compelled to lock thru the auxiliary lock, average processing times nearly doubled.
- Delays (amounting to 15,000 tow hours) greatly exceeded normal levels. Maximum delay to single tow was 104.6 hours.
- After the main chamber re-opened, it took about 94 hours for the queue to dissipate.
- The number of tow arrivals per day increased during the period following announcement of the closure, and decreased during the closure.



Future Surveys



- A Planned Replacement of gate operating machinery is scheduled for the Lock 27 main and auxiliary chambers.
- The auxiliary chamber was closed for eight weeks from 3 October- 27 November 2005, and the main lock chamber will be closed for seven weeks between 3 January and 27 February 2006.



Schedule for Future Surveys



- April June 2006
 - Mail Shippers and Carriers surveys and do a telephone follow up with the companies contacted.
 - Analysis of OMNI data relative to main and auxiliary lock closure at Lock 27.
 - Report including write-up on both the 2005 and 2006 surveys will be available in June 2006.



US Army Corps of Engineers

UMR Locks 27 and Chain of Rocks Canal





One Team: Relevant, Ready, Responsive and Reliable